

REAR PROJECTION TYPE PROJECTOR DEVICE

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a rear projection type projector device that allows a light image projected from a rear side of a screen member to be viewed from a front side of the screen member.

Related Background Art

10 In recent years, a rear projection type projector device has been proposed which allows a light image projected from a rear side of a screen member to be viewed from a front side of the screen member.

15 FIG. 5 is a sectional view showing an example of the structure of a rear projection type projector device.

 Reference numeral 1 denotes a video source (light image output means) and reference numeral 2
20 denotes a reflection mirror (reflecting means). Reference numeral 3 denotes a lenticular screen (screen member), and reference numeral 4 denotes a front plate (transparent member). Reference numeral 5 denotes a Fresnel lens, and reference numeral 6 is
25 a housing. Reference numeral 7 denotes a picture frame-like escutcheon, and reference numerals 8 and 9 denote members for locating at least the screen

member 3 at an opening in the housing 6.

A device D3 comprises the video source (light image output means) 1 that outputs a light image, the reflection mirror (reflecting means) that reflects
5 the light image from the video source 1, and the lenticular screen (screen member) on which the light image reflected by the reflection mirror 2. Thus, the light image projected on the lenticular screen 3 from the rear side (as shown by arrow R) can be
10 viewed from the front side (as shown by arrow F). Reference numeral 4 denotes the transparent member (hereinafter referred to as the "front plate") located in front F of the lenticular screen 3. Reference numeral 5 denotes the Fresnel lens.

15 In spite of its large screen, such a rear projection type projector device requires a smaller depth and a smaller installation area than CRT display devices. Screen device is disclosed, for example, Japanese Patent Application Laid-Open No.
20 H07-209753.

The above described front plate 4 is composed of a relatively rigid member. However, the lenticular screen 3 and the Fresnel lens 5 are only 1 to 2 mm in thickness and are thus not substantially
25 rigid. Furthermore, the lenticular screen 3 and the Fresnel lens 5 are conventionally held vertically with only their ends supported on the housing 6 (see

the members denoted by reference numerals 8 and 9).
Thus, the lenticular screen 3 or the Fresnel lens 5
may be buckled by its own weight to create spaces S
between the front plate 4 and the lenticular screen 3
5 and the Fresnel lens 5. Consequently, resolution may
decrease or the image may be distorted, thus
disadvantageously degrading image quality.

SUMMARY OF THE INVENTION

10 It is thus an object of the present invention
to provide a rear projection type projector device
that prevents a decrease in resolution and the
distortion of an image, thus preventing the
degradation of image quality.

15 Accordingly, the present invention is provided
in view of the above circumstances. There is
provided a rear projection type projector device
comprising light image output means for outputting a
light image, reflecting means for reflecting the
20 light image from the light image output means, and a
screen member on which the light image reflected by
the reflecting means is projected, the device
allowing the light image projected from a rear side
of the screen member to be viewed from a front side
25 of the screen member, the device further comprising:
a transparent member located so as to incline
from a vertical plane,

wherein the screen member is located so as to be placed on the transparent member.

BRIEF DESCRIPTION OF THE DRAWINGS

5 FIG. 1 is a sectional view showing an example of the structure of a rear projection type projector device according to the present invention.

 FIG. 2 is a sectional view showing another example of the structure of a rear projection type
10 projector device according to the present invention.

 FIG. 3 is a detailed sectional view illustrating the angles at which a screen member and the like are mounted in the device shown in FIG. 1.

 FIG. 4 is a detailed sectional view
15 illustrating the angles at which the screen member and the like are mounted in the device shown in FIG. 2.

 FIG. 5 is a sectional view showing an example of the structure of a rear projection type projector
20 device.

 FIG. 6 is a schematic view illustrating problems of a rear projection type projector device.

 Fig. 7 is a front schematic view of a rear projection type projector device according to the
25 present invention.

 Fig. 8 is a view showing an escutcheon and members of a rear projection type projector device

according to the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

An embodiment of the present invention will be
5 described below with reference to FIGS. 1 to 4. In
the Figures, the same reference numerals denote the
same components.

FIG. 1 is a sectional view showing an example
of the structure of a rear projection type projector
10 device D₁ according to the present invention, and
showing a sectional view along the line 1-1 of FIG. 7.
FIG. 2 is a sectional view showing another example of
the structure of a rear projection type projector
device D₂ according to the present invention. FIG. 3
15 is a detailed sectional view illustrating the angles
at which a screen member and the like are mounted in
the device shown in FIG. 1. FIG. 4 is a detailed
sectional view illustrating the angles at which the
screen member and the like are mounted in the device
20 shown in FIG. 2.

The rear projection type projector device
comprises light image output means 1 for outputting a
light image L, reflecting means 2 for reflecting the
light image L from the light image output means 1,
25 and a screen member 3 on which the light image
reflected by the reflecting means 2 is projected.
The light image projected from the rear side (shown

by arrow R and on which the reflecting means 2 is located) of the screen member 3 is viewed from the front side (shown by arrow F) of the screen member 3. Then, as illustrated in FIG. 3, a transparent member 4 is located along the screen member 3. However, the transparent member 4 is located so as to incline from a vertical plane A. Furthermore, almost all the surface of the screen member 3 is placed on the transparent member 4. Here, the vertical plane means a plane (virtual plane) containing a vertical line (this applies to the description below). The expression "screen member 3 is placed on the transparent member 4" means that the screen member 3 is located on a top surface of the transparent member 4 located so as to incline from the vertical plane A so that the transparent member 4 bears the weight of the screen member 3. The screen member 3 and the transparent member 4 may be in contact with each other or another member (for example, a Fresnel lens 5, described later) may be located between the members 3 and 4. In FIGS. 1 and 3, the transparent member 4 is located on the front side of the screen member 3. However, the present invention is not limited to this aspect. The transparent member 4 may be located on the rear side of the screen member 3 as shown in FIGS. 2 and 4.

In this case, the Fresnel lens 5 may be located

on the rear side R of the screen member 3. Almost all the surface of the Fresnel lens 5 may be placed on the transparent member 4 together with the screen member 3. Here, the expression "Fresnel lens 5 is
5 placed on the transparent member 4" means that the Fresnel lens 5 is located on the top surface of the transparent member 4 located so as to incline from the vertical plane A so that the transparent member 4 bears the weight of the Fresnel lens 5. The Fresnel
10 lens 5 and the transparent member 4 may be in contact with each other or another member (for example, the above described screen member 3) may be located between the members 5 and 4.

Furthermore, a housing 6 may be provided to
15 house the light image output means 1 and the reflecting means 2. The screen member 3 and the transparent member 4 (and the Fresnel lens 5) may be supported on the housing 6 at least at their upper ends.

20 Moreover, the above described light image output means 1 may be composed of a light source that emits light and a light bulb that switches the light from the light source to convert it into a light image.

25 The transparent member 4 may be rigid. The screen member 3 may be a lenticular screen.

In the present invention, the transparent

member is a plate and not a frame.

Furthermore, in the present invention, the screen member is thinner than the transparent member. If the transparent member is, for example, a glass
5 plate having a thickness of 3 to 4 mm, then the screen member has a thickness of larger than 0 mm and at most 1.5 mm.

Furthermore, in the present invention, if the above different member is further installed, it is
10 thinner than the transparent member. If the transparent member is, for example, a glass plate having a thickness of 3 to 4 mm, the Fresnel lens, which is the different member, has a thickness of larger than 0 mm and at most 1.5 mm.

15 Description will be given of how the transparent member ensures the planarity of the screen member in the present invention.

If the transparent member is installed so as to extend vertically, the screen member is inevitably
20 buckled perpendicularly to the plane of the screen member (either upward from the front surface or downward from the back surface) under the effect of the gravity.

The inclination of the transparent member means
25 that the buckling of the screen member is prevented to allow the screen member to follow the surface of the planar member. The planar member means that it

is rigid. In the present embodiment, this rigid member corresponds to the transparent member. More specifically, it corresponds to a glass plate of thickness 3 mm or more. The glass plate uses its
5 plane to prevent the buckling of the screen member.

The screen member is also a plate. Owing to its small thickness, the screen member may be buckled when inclined without any supports. The plate can maintain its planarity provided that it is supported
10 on a plane. Any member that fails to take a planar shape when supported on a plane is assumed to be different from the screen member according to the present invention.

In the present invention, the screen member
15 preferably has an inclination θ of larger than 5.5. This will be described below.

An example will be given in which the screen member is used in a rear projection type projector device having a screen for which the ratio of width
20 to length is 16:9, which is comparable to a 64-inch screen. The screen member is composed of methacrylstyrene resin, which is a typical material. The methacrylstyrene has a specific gravity of 1.18. The screen member weighs 1,560 g when its thickness
25 is 1 mm. When the screen member is stood up so that its long horizontal side corresponds to a bottom side and that it is supported from its screen surface to

the degree that it does not fall down, it may be bent (buckled) by 20 to 30 mm. If this bending is avoided by pushing the center of the screen member from the screen surface, a load of about 150 g is required.

5 If the buckling of the screen member is avoided by utilizing the load of the screen member itself without imposing any external loads on it, then it is possible to determine $\theta = 5.5$ on the basis of the relationship $1,560 \times \sin\theta = 150$. θ denotes the angle
10 between the vertical direction and the inclined screen member. Accordingly, it is understandable that the inclination θ is preferably larger than 5.5 if this angle is utilized to avoid the buckling of the screen member itself to maintain its planarity by
15 using the load of the screen member itself without imposing any external loads on the screen member.

FIG. 7 is a front view of the rear projection type projector device shown in FIG. 1. FIG. 1 is a sectional view taken along line 1-1 in FIG. 7. FIG. 2
20 is a sectional view showing another example of the structure of a rear projection type projector device. That is, FIGS. 1 and 2 are schematic sectional views of a central portion of the rear projection type projector device. The same reference numerals as
25 those in the previously described drawings denote the same components. Reference numerals 8a, 8b, 8c and 8d denote members used to locate the screen member.

These members are arranged on the respective sides of the screen member as shown in the figure. The screen member 3, the transparent member 4, and the Fresnel lens 5 are arranged between the members 8 and the escutcheon 7. In particular, to provide for the possible thermal expansion of at least one of the screen member 3, transparent member 4, and Fresnel lens 5, the members 8 other than the lower member 8b, that is, the members 8a, 8c and 8d, are provided with a clearance in the direction of the thermal expansion (more specifically, at the end of each of the screen member 3, transparent member 4, and Fresnel lens 5). The clearance is about 0.1 to 0.2 mm. The clearance is preferably provided to avoid the offset of the screen member in addition to the thermal expansion.

The lengths of the members 8a, 8b, 8c and 8d may be individually determined. More specifically, each of the members 8a, 8b, 8c and 8d preferably has a length equal to or larger than two-thirds of one side of the screen member. This does not mean that the plurality of members are considered to be one member having a length equal to or larger than two-thirds of one side of the screen member but that each member has a continuous length equal to or larger than two-thirds of one side of the screen member. Because of the continuity, the load involved in the sandwiching is uniform within one side. Each of the

members 8a, 8b, 8c and 8d is fixed to the escutcheon using a screw. FIG. 8 is a view showing the escutcheon and the members arranged as described above.

5 The effects of the present embodiment will be described below.

 According to the present embodiment, the screen member 3 is placed and supported on the transparent member 4. This makes it unlikely to create a space
10 between the screen member 3 and the transparent member 4. It is thus possible to prevent a decrease in resolution and the distortion of an image, thus preventing the degradation of image quality.

 Furthermore, the Fresnel lens 5 is located on
15 the rear side R of the screen member 3. When the Fresnel lens 5 is placed on the transparent member 4 together with the screen member 3, it is unlikely created a space between the Fresnel lens 5 and the screen member 3. It is thus possible to prevent a
20 decrease in resolution and the distortion of an image, thus preventing the degradation of image quality.

 The present invention will be described in further detail with reference to examples.

(Example 1)

25 In the present example, the rear projection type projector device D₁, shown in FIGS. 1 and 3, was produced.

In these figures, reference numeral 1 denotes a video source (light image output means) and reference numeral 2 denotes a reflection mirror (reflecting means). Reference numeral 3 denotes a lenticular screen (screen member), and reference numeral 4 denotes a front plate (transparent member). Reference numeral 5 denotes a Fresnel lens. A picture frame-like escutcheon 7 was attached to an opening in a housing 6. The lenticular screen 3, the front panel 4, and the Fresnel lens 5 were attached to the escutcheon 7 using a screw 9 and a presser plate 8. However, the front plate 4 was located so as to incline through an angle θ_1 from a vertical surface A (that is, an upper part of the front plate 4 protrudes toward the front side F). The screen 3 was located on the rear side R of the front plate 4. The Fresnel lens 5 was further placed on the rear side R of the screen 3. Accordingly, the lenticular screen 3 was supported on the front plate 4. However, as shown in FIG. 3, if the weight of the lenticular screen 3 per unit area is defined as w_1 , the lenticular screen 3 is pressed against the front plate 4 under a force $w_1 \sin \theta_1$ (in all the portions of the lenticular screen 3). This makes it unlikely to create a space between the lenticular screen 3 and the front plate 4. That is, the weight w_1 of the lenticular screen 3 can be divided into a component

of force $w\sin\theta_1$ and a component of force $w\cos\theta_1$.
Here, the component of force $w\sin\theta_1$ acts in the
normal direction of the front plate 4. The component
of force $w\cos\theta_1$ acts in the plane direction of the
5 front plate 4. The component of force $w\sin\theta_1$
operates as a force that presses the lenticular
screen 3 itself against the front plate 4. The
lenticular screen 3, which is thin and not rigid, is
in tight contact with the front plate 4, which is
10 very rigid, so as to adhere to the front plate 4.
This also applies to the Fresnel lens 5. The Fresnel
lens 5 is in tight contact with the front plate 4 via
the lenticular screen 3 so as to adhere to the front
plate 4.

15 (Example 2)

In the present example, the rear projection
type projector device D_2 , shown in FIGS. 2 and 4, was
produced. The front plate 4 was located so as to
incline through an angle θ_2 from a vertical surface A
20 (that is, a lower part of the front plate 4 protrudes
toward the front side F). The Fresnel lens 5 was
placed on the front side F of the front plate 4. The
lenticular screen 3 was further placed on the front
side F of the Fresnel lens 5. Accordingly, the
25 Fresnel lens 5 was supported on the front plate 4.
However, as shown in FIG. 4, if the weight of the
Fresnel lens 5 per unit area is defined as w_2 , the

Fresnel lens 5 is pressed against the front plate 4 under a force $w_2 \sin \theta_2$ (in all the portions of the Fresnel lens 5). This makes it unlikely to create a space between the Fresnel lens 5 and the front plate 4. That is, the weight w_2 of the Fresnel lens 5 can be divided into a component of force $w_2 \sin \theta_2$ and a component of force $w_2 \cos \theta_2$. Here, the component of force $w_2 \sin \theta_2$ acts in the normal direction of the front plate 4. The component of force $w_2 \cos \theta_2$ acts in the plane direction of the front plate 4. The component of force $w_2 \sin \theta_2$ operates as a force that presses the Fresnel lens 5 itself against the front plate 4. The Fresnel lens 5, which is thin and not rigid, is in tight contact with the front plate 4, which is very rigid, so as to adhere to the front plate 4. This also applies to the screen 3. The screen 3 is in tight contact with the front plate 4 via the Fresnel lens 5 so as to adhere to the front plate 4.

As described above in the embodiment and examples, according to the present invention, the screen member is placed and supported on the transparent member. This makes it unlikely to create a space between the screen member and the transparent member. It is thus possible to prevent a decrease in resolution and the distortion of an image, thus preventing the degradation of image quality.